

Description

MS3476 series connector

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3476L1210P
Minimum Qty (MOQ):	1
NSN:	5935-00-468-2561
Schedule B:	8535.90.8040
ECCN:	9A991
National Motor Freight:	061680, Elec Wiring Plugs Etc



* See page 2 for technical characteristics

P/N MS3476L12-10P Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Body Style:	Straight Shape, Internal Coupling
Overall Length:	1.420 Inches Maximum
Overall Diameter:	1.043 Inches Maximum
Environmental Protection:	Moisture Resistant And Salt Water Resistant And Vibration Resistant
Threaded Device Type:	Back Shell
Mating End Quantity:	1
Contact Position Arrangement Style:	10-dec Single Mating End
Contact Position Arrangement Style:	12-10 Single Mating End
Contact Removability:	Removable Single Mating End Single Contact Grouping
Contact Maximum Ac Voltage Rating In Volts:	600.0 Single Mating End Single Contact Grouping
Polarization Method:	Keyway Or Multiple Keyway
Insert Position In Deg:	0.0
Shell Type:	Solid
Connector Locking Method:	Bayonet Latch
Nominal Thread Length:	0.290 Inches
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.750 Inches
Terminal Location:	Back Single Mating End Single Contact Grouping
Contact Surface Treatment:	Gold Single Mating End Single Contact Grouping And Nickel Single Mating End Single Contact Grouping
Contact Surface Treatment Document And Classification:	Mil-g-45204 Ty 1,1,grade C Mil Spec 1st Treatment Response Single Mating End Single Contact Grouping And Qq-n-290 Grade E Fed Spec 2nd Treatment Response Single Mating End Single Contact Grouping
Terminal Type:	Crimp Single Mating End Single Contact Grouping
Shell Material:	Aluminum Alloy
Shell Surface Treatment:	Nickel
Shell Surface Treatment Document And Classification:	Mil-c-26074 Cl 3,grade B Mil Spec Single Treatment Response
Included Contact Quantity:	10 Single Mating End Single Contact Grouping

Included Contact Type:	Round Pin Single Mating End Single Contact Grouping
Precious Material And Location:	Contact Surfaces Gold
Precious Material And Weight:	0.050 Gold Grains, Troy
Precious Material:	Gold
Test Data Document:	81349-mil-c-26482 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Unef
Specification/standard Data:	96906-ms3476 Government Standard

How to Order

Order this electrical connector plug from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+connector+plugs/MS3476L12-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.