

Description

MS3476 series connector

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS3476L1210P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5935-00-468-2561 |
| Schedule B: | 8535.90.8040 |
| ECCN: | 9A991 |
| National Motor Freight: | 061680, Elec Wiring Plugs Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS3476L12-10P Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Body Style: | Straight Shape, Internal Coupling |
| Overall Length: | 1.420 Inches Maximum |
| Overall Diameter: | 1.043 Inches Maximum |
| Environmental Protection: | Moisture Resistant And Salt Water Resistant And Vibration Resistant |
| Threaded Device Type: | Back Shell |
| Mating End Quantity: | 1 |
| Contact Position Arrangement Style: | 10-dec Single Mating End |
| Contact Position Arrangement Style: | 12-10 Single Mating End |
| Contact Removability: | Removable Single Mating End Single Contact Grouping |
| Contact Maximum Ac Voltage Rating In Volts: | 600.0 Single Mating End Single Contact Grouping |
| Polarization Method: | Keyway Or Multiple Keyway |
| Insert Position In Deg: | 0.0 |
| Shell Type: | Solid |
| Connector Locking Method: | Bayonet Latch |
| Nominal Thread Length: | 0.290 Inches |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.750 Inches |
| Terminal Location: | Back Single Mating End Single Contact Grouping |
| Contact Surface Treatment: | Gold Single Mating End Single Contact Grouping And Nickel Single Mating End Single Contact Grouping |
| Contact Surface Treatment Document And Classification: | Mil-g-45204 Ty 1,1,grade C Mil Spec 1st Treatment Response Single Mating End Single Contact Grouping And Qq-n-290 Grade E Fed Spec 2nd Treatment Response Single Mating End Single Contact Grouping |
| Terminal Type: | Crimp Single Mating End Single Contact Grouping |
| Shell Material: | Aluminum Alloy |
| Shell Surface Treatment: | Nickel |
| Shell Surface Treatment Document And Classification: | Mil-c-26074 Cl 3,grade B Mil Spec Single Treatment Response |
| Included Contact Quantity: | 10 Single Mating End Single Contact Grouping |

| | |
|--|--|
| Included Contact Type: | Round Pin Single Mating End Single Contact Grouping |
| Precious Material And Location: | Contact Surfaces Gold |
| Precious Material And Weight: | 0.050 Gold Grains, Troy |
| Precious Material: | Gold |
| Test Data Document: | 81349-mil-c-26482 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |
| Thread Series Designator: | Unef |
| Specification/standard Data: | 96906-ms3476 Government Standard |

How to Order

Order this electrical connector plug from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+connector+plugs/MS3476L12-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.