

**Description**

Fastener Length: 35/64", Thread: 6-32, Thread Length: 15/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS34984
Minimum Qty (MOQ):	10
NSN:	5305-01-157-7156
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS3498-4 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.225 Inches Minimum And 0.235 Inches Maximum
<b>Fastener Length:</b>	0.535 Inches Minimum And 0.555 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.255 Inches Minimum And 0.285 Inches Maximum
<b>Head Height:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>First Diameter From Head:</b>	0.084 Inches Minimum And 0.089 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.310 Inches Minimum And 0.320 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5640 Type I Assn Std All Material Responses Overall Or Aisi T-303 Assn Std All Material Responses Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3498-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.