

Description

Fastener Length: 35/64", Thread: 6-32, Thread Length: 15/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS34984
Minimum Qty (MOQ):	10
NSN:	5305-01-157-7156
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS3498-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.225 Inches Minimum And 0.235 Inches Maximum
Fastener Length:	0.535 Inches Minimum And 0.555 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.255 Inches Minimum And 0.285 Inches Maximum
Head Height:	0.060 Inches Minimum And 0.080 Inches Maximum
First Diameter From Head:	0.084 Inches Minimum And 0.089 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.310 Inches Minimum And 0.320 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5640 Type I Assn Std All Material Responses Overall Or Aisi T-303 Assn Std All Material Responses Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3498-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.