

Description

Length: 9/16", Thread: 6-32, Thread Length: 15/64", pan head, washer and nut included, coarse thread, MS3498 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS34988 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-081-0753 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |



* See page 2 for technical characteristics

P/N MS3498-8 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.225 Inches Minimum And 0.235 Inches Maximum |
| Fastener Length: | 0.563 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.260 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.090 Inches Minimum And 0.110 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Special Features: | Standoff Consist Of A Flange And Collar,stud Color Black No. 36231 |
| Material: | Aluminum Alloy 2011 Stand-off |
| Material: | Steel Comp 303 Fastener |
| Material Document And Classification: | Ams 5640 Assn Std Single Material Response Fastener |
| Surface Treatment: | Anodize Stand-off |
| Surface Treatment: | Paint Fastener |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Stand-off |
| Surface Treatment Document And Classification: | Mil-e-15090 Mil Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3498-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.