

## Description


Length: 9/16", Thread: 6-32, Thread Length: 15/64", pan head, washer and nut included, coarse thread, MS3498 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS34988
Minimum Qty (MOQ):	5
NSN:	5305-01-081-0753
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



\* See page 2 for technical characteristics

## P/N MS3498-8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.225 Inches Minimum And 0.235 Inches Maximum
<b>Fastener Length:</b>	0.563 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.260 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.090 Inches Minimum And 0.110 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Special Features:</b>	Standoff Consist Of A Flange And Collar,stud Color Black No. 36231
<b>Material:</b>	Aluminum Alloy 2011 Stand-off
<b>Material:</b>	Steel Comp 303 Fastener
<b>Material Document And Classification:</b>	Ams 5640 Assn Std Single Material Response Fastener
<b>Surface Treatment:</b>	Anodize Stand-off
<b>Surface Treatment:</b>	Paint Fastener
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Stand-off
<b>Surface Treatment Document And Classification:</b>	Mil-e-15090 Mil Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3498-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.