

**Description**

two pole, 20 amps at 28VDC, 20 amps at 115VAC/60Hz, 20 amps at 115VAC/400Hz, with lever seal, screw terminal, heavy duty

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[8822K20](#)

SKU / Model:	MS3505922
Minimum Qty (MOQ):	2
NSN:	5930-00-166-2016
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



\* See page 2 for technical characteristics

## P/N MS35059-22 Specifications

<b>Body Style:</b>	Bushing Mount
<b>Hazardous Locations/environmental Protection:</b>	Weatherproof
<b>Bushing Length:</b>	0.450 Inches Minimum And 0.490 Inches Maximum
<b>Body Length:</b>	1.346 Inches Maximum
<b>Body Width:</b>	1.025 Inches Maximum
<b>Actuator Style:</b>	Round
<b>Actuator Diameter:</b>	0.240 Inches Nominal
<b>Actuator Height:</b>	0.660 Inches Minimum And 0.720 Inches Maximum
<b>Actuator Position-action Relationship:</b>	Up Position Maintained And Down Position Maintained
<b>Maximum Voltage Rating In Volts:</b>	220.0 Ac And 250.0 Dc
<b>Inclosure Type:</b>	Fully Inclosed
<b>Mounting Method:</b>	Threaded Bushing
<b>Features Provided:</b>	Actuator Seal
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.469 Inches
<b>Nonpile-up Contact Arrangement:</b>	2 Pole, Single Throw, Both Positions Maintained Single Switch Unit
<b>Criticality Code Justification:</b>	Feat
<b>Contact Load Current Rating At Maximum Rated Voltage:</b>	500.000 Milliamperes Resistive Dc And 9.000 Amperes Resistive Ac
<b>Special Features:</b>	Item Must Comply With Rqmt Of Desc Production Std No. L00165
<b>Thread Series Designator:</b>	Uns
<b>Terminal Type And Quantity:</b>	4 Tab W/screw

## How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS35059-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.