

Description

two pole, 20 amps at 28VDC, 20 amps at 115VAC/60Hz, 20 amps at 115VAC/400Hz, with lever seal, screw terminal, heavy duty

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[8822K20](#)

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS3505922 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5930-00-166-2016 |
| ECCN: | EAR99 |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



* See page 2 for technical characteristics

P/N MS35059-22 Specifications

| | |
|--|--|
| Body Style: | Bushing Mount |
| Hazardous Locations/environmental Protection: | Weatherproof |
| Bushing Length: | 0.450 Inches Minimum And 0.490 Inches Maximum |
| Body Length: | 1.346 Inches Maximum |
| Body Width: | 1.025 Inches Maximum |
| Actuator Style: | Round |
| Actuator Diameter: | 0.240 Inches Nominal |
| Actuator Height: | 0.660 Inches Minimum And 0.720 Inches Maximum |
| Actuator Position-action Relationship: | Up Position Maintained And Down Position Maintained |
| Maximum Voltage Rating In Volts: | 220.0 Ac And 250.0 Dc |
| Inclosure Type: | Fully Inclosed |
| Mounting Method: | Threaded Bushing |
| Features Provided: | Actuator Seal |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.469 Inches |
| Nonpile-up Contact Arrangement: | 2 Pole, Single Throw, Both Positions Maintained Single Switch Unit |
| Criticality Code Justification: | Feat |
| Contact Load Current Rating At Maximum Rated Voltage: | 500.000 Milliamperes Resistive Dc And 9.000 Amperes Resistive Ac |
| Special Features: | Item Must Comply With Rqmt Of Desc Production Std No. L00165 |
| Thread Series Designator: | Uns |
| Terminal Type And Quantity: | 4 Tab W/screw |

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS35059-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.