

Description

two pole, 20 amps at 28VDC, 20 amps at 115VAC/60Hz, 20 amps at 115VAC/400Hz, with lever seal, screw terminal, heavy duty

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[8822K20](#)

SKU / Model:	MS3505922
Minimum Qty (MOQ):	2
NSN:	5930-00-166-2016
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



* See page 2 for technical characteristics

P/N MS35059-22 Specifications

Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Weatherproof
Bushing Length:	0.450 Inches Minimum And 0.490 Inches Maximum
Body Length:	1.346 Inches Maximum
Body Width:	1.025 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.240 Inches Nominal
Actuator Height:	0.660 Inches Minimum And 0.720 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Maintained
Maximum Voltage Rating In Volts:	220.0 Ac And 250.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Single Throw, Both Positions Maintained Single Switch Unit
Criticality Code Justification:	Feat
Contact Load Current Rating At Maximum Rated Voltage:	500.000 Milliamperes Resistive Dc And 9.000 Amperes Resistive Ac
Special Features:	Item Must Comply With Rqmt Of Desc Production Std No. L00165
Thread Series Designator:	Uns
Terminal Type And Quantity:	4 Tab W/screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS35059-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.