

Description

18 amps at 28VDC, 11 amps at 115VAC/60Hz, Momentary ON - OFF, lever with seal, screw terminal, heavy duty


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[8834K5](#)

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS3505927 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5930-00-615-7882 |
| ECCN: | EAR99 |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



* See page 2 for technical characteristics

P/N MS35059-27 Specifications

| | |
|--|--|
| Unable To Decode: | Unable To Decode |
| Body Style: | Bushing Mount |
| Hazardous Locations/environmental Protection: | Submersible |
| Overall Length: | 1.346 Inches Maximum |
| Overall Height: | 2.410 Inches Nominal |
| Overall Width: | 1.025 Inches Maximum |
| Bushing Length: | 0.470 Inches Nominal |
| Body Length: | 1.346 Inches Maximum |
| Body Width: | 0.430 Inches Maximum |
| Actuator Style: | Round |
| Actuator Diameter: | 0.240 Inches Nominal |
| Actuator Height: | 0.690 Inches Nominal |
| Actuator Position-action Relationship: | Up Position Momentary And Down Position Momentary And Center Position Maintained |
| Maximum Voltage Rating In Volts: | 115.0 Ac And 28.0 Dc |
| End Item Identification: | Missile Minuteman Lgm-30 |
| Mounting Surface To Terminal End Distance: | 1.250 Inches Maximum |
| Inclosure Type: | Fully Inclosed |
| Mounting Method: | Threaded Bushing |
| Features Provided: | Actuator Seal |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.469 Inches |
| Nonpile-up Contact Arrangement: | 2 Pole, Double Throw, Two Positions Momentary Single Switch Unit |
| Contact Load Current Rating At Maximum Rated Voltage: | 18.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 5.000 Amperes Lamp Dc And 11.000 Amperes Resistive Ac And 8.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac |
| Test Data Document: | 81349-mil-dtl-83731 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |
| Thread Series Designator: | Uns |

| | |
|------------------------------------|---------------|
| Terminal Type And Quantity: | 6 Tab W/screw |
|------------------------------------|---------------|

| | |
|-------------------------------------|-----------------------------------|
| Specification/standard Data: | 96906-ms35059 Government Standard |
|-------------------------------------|-----------------------------------|

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS35059-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.