

P/N MS35059-28

Description

two pole, 18 amps at 28VDC, 11 amps at 115VAC/60Hz, with lever seal, screw terminal, momentary ON - OFF

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS3505928

Minimum Qty (MOQ):

NSN: 5930-00-615-7889

ECCN: 9A991

National Motor Freight: 061300, Circuit Breaker / Switch Noi









^{*} See page 2 for technical characteristics

P/N MS35059-28 Specifications

Unable To Decode:	Unable To Decode
Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Submersible
Bushing Length:	0.469 Inches Nominal
Body Length:	1.346 Inches Maximum
Body Width:	0.750 Inches Nominal
Body Height:	1.000 Inches Minimum And 1.250 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.240 Inches Nominal
Actuator Height:	0.657 Inches Minimum And 0.719 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Maintained
Maximum Voltage Rating In Volts:	220.0 Ac And 250.0 Dc
End Item Identification:	Missile Minuteman Lgm-30
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Single Throw, Both Positions Maintained Single Switch Unit
Contact Load Current Rating At Maximum Rated Voltage:	500.000 Milliamperes Resistive Dc And 5.000 Amperes Lamp Dc And 6.000 Amperes Resistive Ac
Test Data Document:	81349-mil-dtl-83731 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Uns
Terminal Type And Quantity:	4 Screw

How to Order

