



★ FASTENERS

Military-Fasteners.com

P/N MS35059-30

Description

two pole, with lever seal, momentary ON - OFF

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[8826K15](#)

SKU / Model:	MS3505930
Minimum Qty (MOQ):	1
NSN:	5930-00-682-3558
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



* See page 2 for technical characteristics

P/N MS35059-30 Specifications

Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Dustproof
Bushing Length:	0.470 Inches Nominal
Body Length:	1.346 Inches Maximum
Body Width:	1.025 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.240 Inches Nominal
Actuator Height:	0.660 Inches Minimum And 0.720 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Momentary
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Single Throw, Normally Open, Momentary Action Single Switch Unit
Criticality Code Justification:	Feat
Contact Load Current Rating At Maximum Rated Voltage:	18.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 5.000 Amperes Lamp Dc And 11.000 Amperes Resistive Ac And 8.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
Special Features:	Item Must Comply With Requirements Of Desc Production Std No. L00733
Thread Series Designator:	Uns
Terminal Type And Quantity:	4 Tab W/screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS35059-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.