

Description



Fastener Length: 5/8", Thread: 2-56, Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190216
Minimum Qty (MOQ):	100
NSN:	5305-00-959-2716
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35190-216 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.589 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.147 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Or Mil-c-81562,type 2 Class 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-216> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.