

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 7/32", cadmium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190235
Minimum Qty (MOQ):	100
NSN:	5305-00-059-4550
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35190-235 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.136 Inches Minimum And 0.229 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:radar Set, Firefinder (an/tpq-36); Trainer, B-1b Aircraft; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Close In Weapon System (ciws-phalanx); Helicopter, Mh-53e; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Armored Security Vehicle, Model Xm1117; Missile, Air Intercept, Sidewinder (aim-9); Air Compressors, High Pressure
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-235> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.