

Description

length: 7/16", thread: 6-32, flat countersunk head, cadmium plated steel, MS35190 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190237
Minimum Qty (MOQ):	100
NSN:	5305-00-059-4552
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35190-237 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.262 Inches Minimum And 0.355 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1011 Or Steel Comp 1013 Or Steel Comp 1010
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-237> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.