

P/N MS35190-241

Military-Fasteners.com

#### Description

Fastener Length: 7/8", Thread: 6-32, Thread Length: 7/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS35190241
Minimum Qty (MOQ):	100
NSN:	5305-00-958-5461
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS35190-241 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.699 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Or Mil-c-81562,type 2 Class 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

## How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS35190-241</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.