

Description

Fastener Length: 1/4", Thread: 8-32, Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS35190249
Minimum Qty (MOQ):	100
NSN:	5305-00-156-2937
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35190-249 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.087 Inches Minimum And 0.192 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.292 Inches Minimum And 0.332 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.070 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Helicopter, Mh-53e; Trainer, B-1b Aircraft; Generator, 60kw, Diesel, Military Standard Family; Aircraft, C-2a (reprocured); Radar Set, Lightweight 3d (an/tps-59); Generator 30kw, Diesel, Military Standard Family; Aircraft, Prowler Ea-6b; Helicopter, Advance Attack, Ah-1w; Teletype, Model 28; Generator, 15kw, Diesel, Military Standard Family
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Or Mil-c-81562 Type 2 Class 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-249> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.