

Description

length: 3/16", thread: 8-32, machine screw, flat countersunk head, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35190250 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-958-5474 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35190-250 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.250 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.292 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel |
| Screw Material Document And Classification: | 66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Or Mil-c-81562,type 2 Class 3 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 2c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-250> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.