

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190253
Minimum Qty (MOQ):	100
NSN:	5305-00-059-4568
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35190-253 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.307 Inches Minimum And 0.400 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.292 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style
Departure From Cited Designator:	As Modified By Material

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-253> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.