

**Description**

Fastener Length: 1-1/2", Thread: 8-32, Thread Length: 1-25/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS35190259                                |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5305-00-957-6640                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS35190-259 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 1.276 Inches Minimum And 1.400 Inches Maximum   |
| <b>Fastener Length:</b>                                     | 1.438 Inches Minimum And 1.500 Inches Maximum   |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>                                       | 0.292 Inches Minimum And 0.332 Inches Maximum   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 60000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                                   | 80.0 Degrees Minimum And 82.0 Degrees Maximum   |
| <b>Screw Material:</b>                                      | Steel   |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response   |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Or Mil-c-81562,type 2,class 3 Mil Spec Single Treatment Response |
| <b>Thread Series Designator:</b>                            | Unc   |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 2c Style   |
| <b>Departure From Cited Designator:</b>                     | As Modified By Material And Tensile Strength  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-259> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.