

**Description**

Fastener Length: 1-1/2", Thread: 8-32, Thread Length: 1-25/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS35190259
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-957-6640
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35190-259 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.276 Inches Minimum And 1.400 Inches Maximum
<b>Fastener Length:</b>	1.438 Inches Minimum And 1.500 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.292 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Screw Material:</b>	Steel
<b>Screw Material Document And Classification:</b>	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Or Mil-c-81562,type 2,class 3 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 2c Style
<b>Departure From Cited Designator:</b>	As Modified By Material And Tensile Strength

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-259> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.