

## P/N MS35190-270

## **Description**

Fastener Length: 7/16", Thread: 10-24, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35190270

Minimum Qty (MOQ): 100

NSN: 5305-00-957-6273

Schedule B: 7318.15.6080


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS35190-270 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.208 Inches Minimum And 0.322 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Or Mil-c-81562,ty 2,cl 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35190-270">https://military-fasteners.com/screws/machine+screws/MS35190-270</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.