



Military-Fasteners.com

P/N MS35190-289L

Description

Fastener Length: 3/4", Thread: 1/4-20, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190289L
Minimum Qty (MOQ):	50 EA
NSN:	5305-01-082-8236
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35190-289L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.466 Inches Minimum And 0.597 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.507 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall Or Mil-c-81562 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-289L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.