

**Description**

Fastener Length: 1-1/2", Thread: 1/4-20, Thread Length: 1-11/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35190293
Minimum Qty (MOQ):	100
NSN:	5305-00-958-5248
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35190-293 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.185 Inches Minimum And 1.347 Inches Maximum
<b>Fastener Length:</b>	1.438 Inches Minimum And 1.500 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.452 Inches Minimum And 0.507 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Screw Surface Treatment:</b>	Cadmium Or Zinc
<b>Screw Surface Treatment Document And Classification:</b>	Sae/ams Qq-p-416 Ty2cl3 Fed Spec Single Treatment Response Or Astm-b633 Ty2cl3 Assn Std Single Treatment Response
<b>Special Features:</b>	Screwmaterial - Steel,carbon
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-293> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.