

Description

Fastener Length: 1-1/2", Thread: 1/4-20, Thread Length: 1-11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35190293
Minimum Qty (MOQ):	100
NSN:	5305-00-958-5248
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35190-293 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.185 Inches Minimum And 1.347 Inches Maximum
Fastener Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Surface Treatment:	Cadmium Or Zinc
Screw Surface Treatment Document And Classification:	Sae/ams Qq-p-416 Ty2cl3 Fed Spec Single Treatment Response Or Astm-b633 Ty2cl3 Assn Std Single Treatment Response
Special Features:	Screwmaterial - Steel,carbon
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35190-293> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.