

Description

Fastener Length: 1/8", Thread: 1-72, Thread Length: 7/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35191207
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-760-3848
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35191-207 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.117 Inches Minimum
Fastener Length:	0.187 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.130 Inches Minimum And 0.146 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.073 Inches
Thread Quantity Per Inch:	72
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-s-416,ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35191-207> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.