

Description

Fastener Length: 3/8", Thread: 2-64, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35191217
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-959-2731
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35191-217 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.147 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	64
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35191-217> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.