

## P/N MS35191-218

### **Description**

Fastener Length: 7/16", Thread: 2-64, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35191218

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-959-6634

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35191-218 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.147 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	64
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35191-218">https://military-fasteners.com/screws/machine+screws/MS35191-218</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.