

Description

length: 1/2, thread: 10-32, machine screw, flat countersunk head, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35191272
Minimum Qty (MOQ):	100
NSN:	5305-01-285-2745
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35191-272 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.291 Inches Minimum And 0.384 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1013 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1017 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1021 Or Steel Comp 1022 Or Steel Comp 1023 Or Steel Comp 1025 Or Steel Comp 1026 Or Steel Comp 1029 Or Steel Comp 1030 Or Steel Comp 1031 Or Steel Comp 1033 Or Steel Comp 1034 Or Steel Comp 1035 Or Steel Comp 1037 Or Steel Comp 1038 Or Steel Comp 1039 Or Steel Comp 1040
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Zinc
Screw Surface Treatment Document And Classification:	Astm B633 Assn Std Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 6 Style
Departure From Cited Document:	As Modified By Surface Treatment

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35191-272> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.