

Description

length: 5/8", thread: 10-32, flat countersunk head, cadmium plated steel, MS35191 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35191273
Minimum Qty (MOQ):	100
NSN:	5305-00-984-7341
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35191-273 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Ch47 Chinook Unique Avionics-qw; Communications Terminal, Satellite An/gsc-39(v)1; Support Equipment, B-1 Aircraft; Engine, Aircraft F110-ge-400; Aviation Engine Test Systems (aets); Deep Submergence Systems Programs (dssp); Helicopter, Mh-53e; Aircraft, C-2a (reprocured); Fire Pumps; Torpedo, Mk 48
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35191-273> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.