

Description


length: 3/4", thread: 10-32, flat countersunk head, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35191274 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-984-7342 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35191-274 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.688 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.340 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | Mrap Buffalo Mk2a2 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35191-274> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.