

**Description**

Fastener Length: 1/8", Thread: 2-56, Thread Length: 3/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS351981
Minimum Qty (MOQ):	70 EA
NSN:	5305-00-052-5945
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N MS35198-1 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.038 Inches Minimum
<b>Fastener Length:</b>	0.125 Inches Nominal
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.156 Inches Minimum And 0.172 Inches Maximum
<b>Head Height:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Countersink Angle:</b>	82.0 Degrees Nominal
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 2c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35198-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.