



Military-Fasteners.com

P/N MS35198-1

Description

Fastener Length: 1/8", Thread: 2-56, Thread Length: 3/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS351981
Minimum Qty (MOQ):	70 EA
NSN:	5305-00-052-5945
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS35198-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.038 Inches Minimum
Fastener Length:	0.125 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Head Height:	0.028 Inches Minimum And 0.036 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35198-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.