

P/N MS35198-14

Description

Fastener Length: 3/8", Thread: 4-40, Thread Length: 21/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS3519814

Minimum Qty (MOQ): 20

NSN: 5305-00-151-1319

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









^{*} See page 2 for technical characteristics

P/N MS35198-14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.325 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.200 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Fms-a7 Aircraft; An/srn-25(v) Navigation Radio Set; Fms-know Class Ff; Helicopter, Mh-53e; Helicopter, Advance Attack, Ah-1w; Arc-182 Airborne Radio, Communication; Helicopter, Seahawk, H-60; F4s Aircraft; Helicopter, Carrier Based Asw, Sh-60f; Tarawa Class Lha
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35198-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.