

## P/N MS35198-32

## **Description**

Fastener Length: 1-1/4", Thread: 6-32, Thread Length: 1-3/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3519832

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-052-6682

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35198-32 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.105 Inches Minimum
Fastener Length:	1.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.257 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	550000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35198-32">https://military-fasteners.com/screws/machine+screws/MS35198-32</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.