

P/N MS35198-69

Military-Fasteners.com

Description

Fastener Length: 1/2", Thread: 1/4-20, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS3519869
Minimum Qty (MOQ):	1000 EA
NSN:	5305-00-052-5923
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



P/N MS35198-69 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Astm B16 Assn Std Single Material Response Or Astm B36 Assn Std Single Material Response Or Astm B121 Assn Std Single Material Response Or Astm B124 Assn Std Single Material Response
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	Mil-f-495 Mil Std Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS35198-69</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.