

Description

Fastener Length: 5/8", Thread: 1/4-20, Thread Length: 5/8", MS35198 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS3519870 |
| Minimum Qty (MOQ): | 250 |
| NSN: | 5305-00-206-3689 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |



P/N MS35198-70 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.525 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.452 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35198-70> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.