

Description

Fastener Length: 3/32", Thread: 0-80, Thread Length: 7/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35199109
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-904-8308
Schedule B:	8535.90.8040
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N MS35199-109 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.100 Inches Minimum
Fastener Length:	0.094 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.099 Inches Minimum And 0.119 Inches Maximum
Head Height:	0.018 Inches Minimum And 0.025 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35199-109> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.