

Description

Fastener Length: 3/8", Thread: 4-48, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS3519914 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-899-2745 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N MS35199-14 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.333 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.195 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 48 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35199-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.