

## P/N MS35206-218

### **Description**

length: 5/8", thread: 4-40, pan head, cadmium plated carbon steel, coarse thread, MS35206 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35206218

Minimum Qty (MOQ): 100

NSN: 5305-00-983-6730

Schedule B: 7318.15.4000

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









# P/N MS35206-218 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.575 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy 268 And Copper Alloy 360
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35206-218">https://military-fasteners.com/screws/machine+screws/MS35206-218</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.