

## P/N MS35206-218Z

### **Description**

MS35206-218Z Machine Screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35206218Z

Minimum Qty (MOQ): 100

NSN: 5305-01-566-6330

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35206-218Z Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type lii
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Zinc
Screw Surface Treatment Document And Classification:	Astm B633-78 Assn Std Single Treatment Response
Thread Series Designator:	Unc

# **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35206-218Z">https://military-fasteners.com/screws/machine+screws/MS35206-218Z</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS35206-218Z">https://military-fasteners.com/screws/machine+screws/MS35206-218Z</a> and selecting the quantity you