

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 3/8", MS35206 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS35206228Z |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-570-6440 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS35206-228Z Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Nominal |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | Mrap,rg33 Caiman |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel |
| Screw Surface Treatment: | Zinc |
| Screw Surface Treatment Document And Classification: | Astm B633-78, Fe/zn 5, Type Ii Assn Std Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-228Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.