

**Description**

Fastener Length: 1/4", Thread: 8-32, Thread Length: 5/8", MS35206 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35206246Z
Minimum Qty (MOQ):	100
NSN:	5305-01-300-7444
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35206-246Z Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	6000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 1013 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1017 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1021 Or Steel Comp 1022
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Zinc
<b>Screw Surface Treatment Document And Classification:</b>	Astm B633,ty 2 Cl Fe/zn 13 Assn Std Single Treatment Response
<b>Special Features:</b>	Screw Material Continue All Steel Comp For 1023 Or 1025 Or 1026 Or 1029 Or 1030 Or 1031 Or 1033 Or 1034 Or 1037 Or 1038 Or 1039 Or 1040
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style
<b>Departure From Cited Document:</b>	As Modified By Surface Treatment

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-246Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.