

Description

length: 5/8, thread: 10-24, pan head, cadmium plated carbon steel, coarse thread, MS35206 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35206264 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-984-6211 |
| Schedule B: | 7318.15.4000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35206-264 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| iii End Item Identification: | Mrap M-atv Socom |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Surface Treatment: | Zinc |
| Screw Surface Treatment Document And Classification: | Astmb633 Assn Std Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-264> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.