

# P/N MS35206-264

### **Description**

length: 5/8, thread: 10-24, pan head, cadmium plated carbon steel, coarse thread, MS35206 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35206264

Minimum Qty (MOQ): 100

NSN: 5305-00-984-6211

Schedule B: 7318.15.4000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35206-264 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
lii End Item Identification:	Mrap M-atv Socom
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Zinc
Screw Surface Treatment Document And Classification:	Astmb633 Assn Std Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35206-264">https://military-fasteners.com/screws/machine+screws/MS35206-264</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.