

Description

Fastener Length: 3-", Thread: 10-24, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35206275 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-984-7365 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS35206-275 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.750 Inches Minimum |
| Fastener Length: | 3.000 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-275> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.