

**Description**

Fastener Length: 3-", Thread: 10-24, Thread Length: 1-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS35206275                                |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-984-7365                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS35206-275 Specifications

|                                                             |                                                       |
|-------------------------------------------------------------|-------------------------------------------------------|
| <b>Thread Class:</b>                                        | 2a                                                    |
| <b>Thread Direction:</b>                                    | Right-hand                                            |
| <b>Thread Length:</b>                                       | 1.750 Inches Minimum                                  |
| <b>Fastener Length:</b>                                     | 3.000 Inches Nominal                                  |
| <b>Head Style:</b>                                          | Pan                                                   |
| <b>Head Diameter:</b>                                       | 0.357 Inches Minimum And 0.373 Inches Maximum         |
| <b>Head Height:</b>                                         | 0.122 Inches Minimum And 0.133 Inches Maximum         |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                   |
| <b>Nominal Thread Diameter:</b>                             | 0.190 Inches                                          |
| <b>Thread Quantity Per Inch:</b>                            | 24                                                    |
| <b>Minimum Tensile Strength:</b>                            | 55000 Pounds Per Square Inch                          |
| <b>Screw Material:</b>                                      | Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013 |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std All Material Responses                     |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| <b>Thread Series Designator:</b>                            | Unc                                                   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-275> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.