

P/N MS35206-282Z

Military-Fasteners.com

Description

Fastener Length: 1/16", Thread: 1/4-20, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS35206282Z
Minimum Qty (MOQ):	75 EA
NSN:	5305-01-571-7799
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N MS35206-282Z Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	0.0875 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.750 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Mrap - Unique Nsn - Rg33 Cat I
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, machine
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Zinc
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Туре

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS35206-282Z</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.