

Description

Fastener Length: 1/16", Thread: 1/4-20, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS35206282Z |
| Minimum Qty (MOQ): | 75 EA |
| NSN: | 5305-01-571-7799 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS35206-282Z Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Nominal |
| Fastener Length: | 0.0875 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.750 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | Mrap - Unique Nsn - Rg33 Cat I |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Screw,machine |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Zinc |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-282Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.