

Description

Fastener Length: 1/2", Thread: 1/4-18, Thread Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35206294
Minimum Qty (MOQ):	50
NSN:	5305-00-984-5674
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35206-294 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.615 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35206-294> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.